

External Extreme



FITTING INSTRUCTIONS

To complete the installation of your External Extreme Factory Finished Door, please adhere strictly to the following, to meet the conditions of our 10 year guarantee.

WITHOUT EXCEPTION, ANY ADJUSTMENT TO THIS DOOR MUST BE IMMEDIATELY RESEALED WITH A PROPRIETARY BRAND OF PRIMER AND PAINT. NO TIMBER SHOULD BE LEFT EXPOSED TO THE ELEMENTS!



1. Trimming

Any adjustment to the dimensions of the door must be in line with the following advice:

- Height adjustment must be ONLY made from the top of the door, to a maximum of 10mm.
- Width adjustment must be made EQUALLY from the sides of the door, to a maximum of 5mm from each side.

2. Threshold

It is acceptable to fit a Rebated Threshold product to the bottom of this door, following the manufacturer's instructions. It is recommended that the rebate be not more than approximately 12-15mm from the bottom of the door

3. Hinges and Locks.

The Fitting of three hinges should be in the positions as follows. Exterior doors should be hinged between 125-150mm (5-6 inches) from the top and 175-230mm (7-9 inches) from the bottom of the door, with a third hinge in the middle of the door. We recommend the use of stainless steel hinges with minimum blade sizes 100mm (4 inches). Care should be taken when chiselling out the recesses for the hinges.

Locks – the lock may be positioned on either side of the door. If you have trimmed off the maximum allowance of 5mm from the door edge, then there will be 95mm of timber available for your mortise lock to be cut into. It is recommended that any screw fixings should be no more than 90mm from the door edge.

Door Knocker or similar – any accessory should be fitted towards the stile of the door, rather than centrally upon the door following the instructions given above in regards to the lock.

4. The Fitting of a Letter Box

This door CAN ONLY be fitted with a 2-Part Letter Box. After fitting please ensure that a bead of silicone is applied all around the letter box to reseal the door. Failure to do so will invalidate our guarantee

5. Weather Bar

The Fitment of a Weather bar is essential to aid the protection of the bottom of the door - we recommend the use of an Aluminium Weather bar as supplied with the door.

6. Finishing

This door is supplied factory finished in white. Any trimming or recess cuts for hinges and locks will expose the door to possible moisture ingress if left untreated. Ensure that all areas that have been cut are appropriately sealed again before hanging. Should you wish to change the final colour of your door, simply apply a further Top Coat of your preferred colour.

7. Recoating

Depending upon its exposure and location, your door will need redecorating periodically with a good quality paint to maintain its appearance. Please consult with your decorating supplier for assistance.

8. Glazing

If your door has been supplied with factory installed glazing, please follow instruction according to the label, which states which face should be placed externally to maximise the efficiency of the double glazed unit.

Fitting a Letter Box



For full details of your 10 year product guarantee, please refer to www.jbkind.com

INSPIRATIONAL DOORS.
Undeniable value.

Tel: 01283 554197
www.jbkind.com

J/B/Kind
DOORS